

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
15 January 2004 (15.01.2004)

PCT

(10) International Publication Number  
**WO 2004/005722 A1**

- (51) International Patent Classification<sup>7</sup>: **F04D 5/00, 23/00**
- (21) International Application Number:  
PCT/GB2003/002907
- (22) International Filing Date: 4 July 2003 (04.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0215709.7 5 July 2002 (05.07.2002) GB
- (71) Applicant (for all designated States except US): **THE BOC GROUP PLC** [GB/GB]; Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **STONES, Ian, David** [GB/GB]; 4 The Oaks, Burgess Hill, West Sussex RH15 9XP (GB). **GRAHAM, Ingo** [GB/GB]; 55 Lyndhurst Road, Hove, East Sussex BN3 6FD (GB).
- (74) Agent: **WICKHAM, Michael**; The Boc Group Plc, Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A REGENERATIVE FLUID PUMP AND STATOR FOR THE SAME



(57) Abstract: A regenerative fluid pump (10) comprises a rotor having rotor blades for compressing fluid on two fluid flow paths, the first of which extends between a first pump inlet (12a) and a first pump outlet (14a), and a second of which extends between a second pump inlet (12b) and a second pump outlet (14b). The pump comprises a stator comprising a plurality of concentric channels (16), each of which comprises: a pumping channel portion (18) along which said rotor blades move for compressing said fluid between an inlet and an outlet of the pumping channel; and a stripper channel portion (20) (shown in broken lines) which allows movement of said rotor blades from said outlet to said inlet of the pumping channel portion. Each concentric channel (16) comprises two pumping channel portions (18) and two stripper channel portions (20).

- 1 -

**A REGENERATIVE FLUID PUMP AND STATOR FOR THE SAME**

The present invention relates to a regenerative fluid pump.

A regenerative fluid pump known hereto is shown schematically in Figure 3. The prior art pump 100 is a radial regenerative fluid pump which compresses fluid on a single fluid flow path extending between an inlet 102 and an outlet 104 of the pump. The pump comprises a plurality of concentric circumferential channels 105 (represented by concentric circles in Figure 3). The channels comprise respective pumping channel portions 106 along which fluid compression takes place and which together form part of the fluid flow path. The channels further comprise respective stripper channel portions 108 (shown in broken lines) which allow the passage of the pump's rotor blades from the outlets of respective pumping channel portions 106 to the inlets thereof.

In operation, fluid enters the pump inlet 102 and is compressed by the rotor blades in the radially outermost, or first, pumping channel portion 106a. At the outlet of the first pumping channel portion, fluid is diverted by a diversion channel 110 (shown by arrows in Figure 3) to the inlet of a radially inner, or second, pumping channel portion 106b. At this time, rotor blades having passed along the first pumping channel 106a move into the radially outermost, or first, stripper channel portion 108a and back to the inlet of the first pumping channel 106a. Although most fluid is diverted radially inwardly by the diversion channel there is some seepage through the stripper channel portion due to the action of the rotor blades and the pressure gradient from the inlet to the outlet of the stripper channel portion. The stripper channel portion is made so that there are small running clearances between the walls of the stripper channels and rotor blades passing therethrough.

- 2 -

Fluid continues along the fluid flow path in the same manner as described above until it reaches the pump outlet 104 and for brevity this further operation will not be described.

It is desirable in certain circumstances to increase the pumping capacity of the regenerative pump 100 described above. Figure 4 is a schematic view of a further prior art regenerative fluid pump 200 in which pumping capacity has been increased. Both pumps 100 and 200 are four stage pumps but unlike pump 100, pump 200 has two fluid flow paths between two pump inlets 202a and 202b and one pump outlet 204. The pump inlets 202a and 202b allow fluid to enter the first pumping channel portion 206a and 206b, respectively, where compression by the rotor blades takes place. This constitutes the first pumping stage of the pump and as it will be appreciated, pumping capacity increased by the use of parallel pumping channel portions 206a, 206b. In operation, fluid is diverted from the outlets of both the first and the second pumping channel portions 206a, 206b to the inlet of the third pumping channel portion 206c by first and second diversion channels 210a and 210b, respectively. Fluid from both the first and the second pumping channels 206a, 206b is then compressed in the third pumping channel portion 206c which constitutes the second pumping stage of pump 200. Fluid continues to be compressed along the fluid flow path until it reaches the pump outlet 204, in the same manner as with pump 100 above. The arrangement of pump 200 allows the pumping capacity to be increased.

The problems with pump 200 are that the additional pumping channel portion requires the pump to be larger and more massive, requiring increased manufacturing. Power requirements also increase and performance characteristics deteriorate.

It is desirable to provide a regenerative fluid pump with increased capacity, without some or all of the above mentioned problems.

- 3 -

The present invention provides a regenerative fluid pump comprising a rotor having rotor blades, and a stator comprising a plurality of concentric channels which comprise pumping channel portions along which said rotor blades move for compressing fluid between respective inlets and respective outlets of the pumping channel portions and stripper channel portions for allowing said rotor blades to pass from said outlets to said inlets of the pumping channel portions, wherein at least one of said concentric channels comprises at least two pumping channel portions and at least two stripper channel portions.

The present invention also provides a stator for a regenerative fluid pump comprising a rotor having rotor blades, the stator comprising a plurality of concentric channels which comprise pumping channel portions along which said rotor blades move for compressing fluid between respective inlets and respective outlets of the pumping channel portions and stripper channel portions for allowing said rotor blades to pass from said outlets to said inlets of the pumping channel portions, wherein at least one of said concentric channels comprises at least two pumping channel portions and at least two stripper channel portions.

Other aspects of the invention are defined in the accompanying claims.

In order that the present invention may be well understood, an embodiment thereof, will now be described, with reference to the accompanying drawings, in which:

Figure 1 is a schematic representation of a regenerative fluid pump embodying the present invention;

Figure 2 is a schematic representation of another regenerative fluid pump embodying the present invention;

Figure 3 is a schematic view of a prior art regenerative fluid pump; and

- 4 -

Figure 4 is a schematic view of another prior art regenerative fluid pump.

Referring to Figure 1, a regenerative fluid pump 10 is shown which comprises four pumping stages although, more or less stages may be provided, as required. Pump 10 comprises a rotor (not shown) having rotor blades for compressing fluid on two fluid flow paths, the first of which extends between a first pump inlet 12a and a first pump outlet 14a, and a second of which extends between a second pump inlet 12b and a second pump outlet 14b. The pump comprises a stator comprising a plurality of concentric channels 16, each of which comprises: a pumping channel portion 18 along which said rotor blades move for compressing said fluid between an inlet and an outlet of the pumping channel; and a stripper channel portion 20 (shown in broken lines) which allows movement of said rotor blades from said outlet to said inlet of the pumping channel portion. Diversion channels 22 (indicated by arrows in Figure 1) divert fluid between the pumping channel portions in the same way as the diversion channels described above in relation to Figure 3.

Differently from the prior art, each concentric channel 16 comprises two pumping channel portions 18 and two stripper channel portions 20. Each channel 16 forms part of both fluid flow paths, although at diametrically opposed parts of the channel. Although each of the pumping channel portions 18 in respective concentric channels is shorter (extends over a reduced arc) as compared with the pump shown in Figure 3, it has been found that most compression takes place over the latter portion of a pumping channel portion and therefore the reduction in length does not significantly affect compression ratio in the pumping channel portions. Accordingly, the capacity of the pump 10 is almost doubled as compared to the capacity of the pump 100 shown in Figure 3. Reference is made to the Applicant's co-pending application (GB0215708.9) in which the effect of reducing the length of the pumping channel portion length is discussed in more detail.

- 5 -

In operation, fluid enters the first fluid flow path and the second fluid flow path at first pump inlet 12a and second pump inlet 12b, respectively. Fluid on the first fluid flow path is compressed by rotor blades passing along a first pumping channel portion 18a forming part of an outermost, or first, concentric channel 16a. At the outlet of the first pumping channel portion 18a, a diversion channel 22 diverts fluid to a radially inner, or second, concentric channel 16b and to an inlet of a first pumping channel portion 18b in channel 16b. Simultaneously, fluid on the second fluid flow path is compressed by rotor blades passing along a second pumping channel portion 18a' forming part of the outermost, or first, concentric channel 16a. At the outlet of the second pumping channel portion 18a', a diversion channel 22 diverts fluid to the radially inner, or second, concentric channel 16b and to an inlet of a second pumping channel portion 18b' in channel 16b. Respective stripper channel portions 20a and 20a' allow rotor blades to pass between the inlet and the outlet of pumping channel portions 18a and 18a'.

Fluid continues along both first fluid flow paths in the same way as described above with reference to the outermost, or first, concentric channel 16a until the fluid reaches pump outlets 14a and 14b where it is exhausted from the pump 10.

In pump 10, each concentric channel 16 comprises two pumping channel portions 18 and two stripper channel portions 20. However, it will be appreciated that increased pumping capacity will be achieved if only some or one concentric channel is provided with this parallel pumping arrangement. In figure 2, a pump 30 is shown in which the two radially outer concentric channels each have two pumping channel portions (shown in solid lines) and two stripper channel portions (shown in broken lines), whereas the two radially inner concentric channels have one pumping channel portion (shown in partially broken lines) and one stripper channel portion (shown in broken lines).

- 6 -

Fluid flows along a first fluid flow path extending from a first pump inlet 32a to a single pump outlet 34, and along a second fluid flow path extending from a second pump inlet 32b to the pump outlet 34. At the radially inner concentric channels, the first and the second fluid flow paths merge.

As with pump 10, fluid flowing on the first fluid flow path travels along respective first pumping channel portions 38a, 38b in first and second concentric channels 36a, 36b. At the outlet of the first pumping channel portion 38b in the second concentric channel 36b, fluid is diverted inwardly by a diversion channel 41 to the third concentric channel 36c and to a secondary inlet 42 in pumping channel portion 38c. Inlet 42 is situated approximately half way along the length of pumping channel portion 38c. Fluid flowing on the second fluid flow path travels along respective second pumping channel portions 38a', 38b' in first and second concentric channels 36a, 36b. At the outlet of the second pumping channel portion 38b' in the second concentric channel 36b, fluid is diverted inwardly by a diversion channel 41 to the third, or radially inner, concentric channel 36c and to a primary inlet 44 in pumping channel portion 38c. Inlet 44 is situated at the start of pumping channel portion 38c. First and second fluid flow paths merge at secondary inlet 42. At outlet 46 of pumping channel portion 38c, fluid is diverted inwardly by a diversion channel 41 to fourth, or radially innermost, concentric channel 36d and to the inlet 48 of the fourth pumping channel portion 38d where the fluid is compressed over the final stage of the pump 30 and exhausted through pump outlet 34.

Stripper channel portions 40c and 40d allow the passage of rotor blades from the outlets to the inlets of respective pumping channel portions 38c and 38d.

- 7 -

Pump 30 provides increased pumping capacity as compared with prior art pump 100 but provides less capacity than pump 10. With the parallel arrangement of fluid flow paths described in relation to Figures 1 and 2, pumping capacity can readily be changed by changing the stator of a pump. This is because the rotor is the same and the rotor blades are the same size from pump to pump. For instance, if it is desired to increase the capacity of pump 100 shown in Figure 3, the stator can be replaced by the stator of pump 10 or pump 30. This means that variations in pumping capacity can be achieved at relatively lower costs. It will also be appreciated that the pumps shown in Figures 1 and 2 achieve increased capacity without significant changes in pump size or mass, and without substantial increases in power requirements.

As shown in Figure 1, two pumping channel portions are provided in each concentric channel. It is possible to provide more than two such pumping channel portions in each or one of the concentric channels, providing the required compression is achieved in each pumping channel portion.

Figure 1 shows a radial regenerative fluid pump with increased pumping capacity. However, the present invention also relates to an axial regenerative fluid pump, in which the concentric channels are arranged axially as opposed to radially.



- 8 -

CLAIMS

1. A regenerative fluid pump comprising a rotor having rotor blades, and a stator comprising a plurality of concentric channels which comprise pumping channel portions along which said rotor blades move for compressing fluid between respective inlets and respective outlets of the pumping channel portions and stripper channel portions for allowing said rotor blades to pass from said outlets to said inlets of the pumping channel portions, wherein at least one of said concentric channels comprises at least two pumping channel portions and at least two stripper channel portions.
2. A regenerative fluid pump as claimed in claim 1, wherein each of said concentric channels comprises at least two pumping channel portions and at least two stripper channel portions such that two fluid flow paths are formed between respective pump inlets and respective pump outlets.
3. A regenerative fluid pump as claimed in claim 1 or 2, comprising two pump inlets for allowing fluid into respective pumping channel portions of a radially outermost said concentric channel.
4. A regenerative fluid pump as claimed in claim 1, wherein one or more radially inner said concentric channels each comprise a single said pumping channel portion and a single said stripper channel portion.
5. A regenerative fluid pump as claimed in claim 4, wherein one of said single pumping channel portions comprises two inlets.

- 9 -

6. A stator for a regenerative fluid pump comprising a rotor having rotor blades, the stator comprising a plurality of concentric channels which comprise pumping channel portions along which said rotor blades move for compressing fluid between respective inlets and respective outlets of the pumping channel portions and stripper channel portions for allowing said rotor blades to pass from said outlets to said inlets of the pumping channel portions, wherein at least one of said concentric channels comprises at least two pumping channel portions and at least two stripper channel portions.
7. A regenerative fluid pump substantially as hereinbefore described with reference to Figures 1 and 2 of the accompanying drawings.
8. A stator for a regenerative fluid pump the stator being substantially as hereinbefore described with reference to Figures 1 and 2 of the accompanying drawings.

1 / 2




FIG. 1






FIG. 2

2 / 2



**FIG. 3**  
PRIOR ART



**FIG. 4**  
PRIOR ART

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 03/02907

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 F04D5/00 F04D23/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 F04D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 253 246 A (DOWTY DEFENCE & AIR SYST) 2 September 1992 (1992-09-02) page 15, paragraph 3 -page 17, paragraph 2; figure 6	1-3,6-8
X	US 4 678 395 A (SCHWEINFURTER FRIEDRICH) 7 July 1987 (1987-07-07) column 4, line 14 - line 49; figure 2	1-3,6-8
X	PATENT ABSTRACTS OF JAPAN vol. 1995, no. 08, 29 September 1995 (1995-09-29) -& JP 07 127595 A (NIPPON SOKEN INC), 16 May 1995 (1995-05-16) abstract; figure 9	1-3,6-8
	---	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

1 October 2003

Date of mailing of the international search report

13/10/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Di Giorgio, F

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 03/02907

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 917 431 A (ROSE WILLIS EARL) 4 November 1975 (1975-11-04) column 4, line 58 -column 5, line 11; figure 7 -----	1,2,6-8

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 03/02907

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2253246	A	02-09-1992	EP 0515632 A1 WO 9210681 A1 JP 5505011 T	02-12-1992 25-06-1992 29-07-1993
US 4678395	A	07-07-1987	DE 3427112 A1 AT 64772 T CS 8505362 A2 DD 237533 A5 DE 3583312 D1 EP 0170175 A2 JP 1911677 C JP 6031634 B JP 61087996 A	23-01-1986 15-07-1991 15-01-1988 16-07-1986 01-08-1991 05-02-1986 09-03-1995 27-04-1994 06-05-1986
JP 07127595	A	16-05-1995	NONE	
US 3917431	A	04-11-1975	BE 819401 A1 CA 1002386 A1 DE 2445157 A1 FR 2244088 A1 GB 1476518 A IT 1019236 B JP 50056606 A	16-12-1974 28-12-1976 20-03-1975 11-04-1975 16-06-1977 10-11-1977 17-05-1975